

**DECLARATION OF PERFORMANCE (DoP)**  
Repar SM



1. **Unique identification code of the product-type:** Repar SM
2. **Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):** lot number shown on the packing
3. **Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:** UNI EN 1504/3 Products and systems for the protection and repair of concrete structures - Structural and non-structural repair - Leveling cementitious adhesive, moldable, thixotropic, rapid curing
4. **Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):** Azichem Srl - via G. Gentile, 16/A - 46044 Goito (MN) – ITALY
5. **Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):** Not applicable
6. **System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:** 2+
7. **In case of the declaration of performance concerning a construction product covered by a harmonized standard:** Tecnoprove Srl (0925) it issued the certificate of conformity of Factory Production Control (n° 67/2013), relying on the following elements:
  - I. Initial inspection of the manufacturing plant and factory production control;
  - II. Monitoring, assessment and evaluation of the factory production control.
8. **In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:** Not applicable
9. **Declared performance:**

Essential characteristics	Performance	Harmonized technical specification
Compressive strength	Class R4	UNI EN 1504-3
Chloride ion content	≤ 0,05%	
Adhesive Bond	1,2 MPa	
Restrained shrinkage / expansion (dimensional stability)	NPD	
Carbonation Resistance	Pass	
Elastic Modulus	NPD	
Thermal Compatibility	≥ 1,5 MPa	
Skid resistance	Class III	
Coefficient of thermal expansion	NPD	
Capillary absorption	0,58 kg · m <sup>-2</sup> · h <sup>-0,5</sup>	
Reaction to fire	A1	
Dangerous substances	see SDS	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Manufacturer's signature  
 Giuseppe Pattarini
 